



GE Plastics

MATERIAL SAFETY DATA SHEET

LEXAN® THERMOCLICK / THERMOCLEAR® SHEET

Revision : 04/08/1998,

Supercedes issue : na

Page : 1/4

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

MANUFACTURER / SUPPLIER

GE Plastics
Plasticslaan 1, P. O. Box 117
4600 AC Bergen op Zoom
The Netherlands

TELEPHONE

During office hours: (31)-164-292046 (24 hr) ; After office hours: (31)-164-292911 (24 hr).

PRODUCT IDENTIFIER : LEXAN® THERMOCLICK® (LTC) Sheet.
DESCRIPTION : Multi-wall polycarbonate (PC) thermoplastic sheet, with UV surface protection.
PRODUCT USE : Main polymer: Poly (bisphenol-A carbonate), CAS 24936-68-3.
: As sheet for flat glazing applications.

2. COMPOSITION / INFORMATION ON INGREDIENTS

This product consists primarily of high molecular weight polymers which are not expected to be hazardous.

3. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Eyes : Small particles may cause irritation / injury due to mechanical action.
Skin : Product not likely to cause skin irritation.
Ingestion : Not acutely toxic.
Inhalation : Product inhalation unlikely due to physical form.
Melt processing health effects : Molten plastic can cause severe burns.
: Processing fumes may cause irritation to the eyes, skin and respiratory tract, and in cases of severe over-exposure, nausea and headache.
Medical restrictions : When heated up to processing temperatures virtually all thermoplastics emit processing fumes. The exact composition and concentration of these processing fumes depend on the sheet formulation, including additives, the residence time in the processing equipment, equipment variables such as venting parameters and the processing temperature. When the product is processed according to GE Plastic's recommended guidelines (available on request) and taking normal precautions detailed below, there are no known adverse effects to human health. Certain sensitive individuals and those with respiratory impairments, however, may experience some temporary irritation by exposure to specific components in the processing fumes.

LEXAN® THERMOCLICK / THERMOCLEAR® SHEET

Revision : 04/08/1998,

Supersedes issue : na

Page : 2/4

4. FIRST AID MEASURES

- Eyes : Remove contact lenses at once. Immediately flush eyes well with copious quantities of water or normal saline solution for 20-30 minutes. If irritation persists, seek medical attention.
- Skin : No first aid required.
- Ingestion : Since this material is not expected to be an ingestion problem, no first aid procedures are required.
- Inhalation : Not likely to be inhaled due to physical form.
- Thermal processing : For molten plastic skin contact, cool rapidly with water and seek immediate medical attention. Do not attempt removal of plastic without medical assistance. Do not use solvent for removal.
: For processing fume inhalation irritation, leave contaminated area and breathe fresh air. If coughing, difficulty in breathing or any other symptoms develop, seek medical attention at once.

5. FIRE FIGHTING MEASURES

- Fire fighting : Approved pressure demand breathing apparatus and protective clothing should be used for all fires.
- Extinguishing media : This product will melt but will not be carried on the surface of water.
: Water spray and foam are recommended. Water is the best extinguishing medium.
: Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition.
- Hazardous combustion : Hazardous combustion products may include intense heat, dense black smoke, carbon monoxide, carbon dioxide and traces of hydrocarbon fragments.
- Conditions of flammability : Requires a continuous flame source to ignite and sustain burning.
- Explosion data
- Impact sensitivity : Not sensitive to mechanical impact.
 - Static discharge : Not sensitive to static discharge.

6. ACCIDENTAL RELEASE MEASURES

- General : Sweep or gather up material and place in proper container for disposal or recovery (See Disposal Information).

7. HANDLING AND STORAGE

- Handling : Follow good standard industrial hygiene practices. Apply adequate ventilation directly to the outside air.
- Storage : Inert material under normal storage conditions. No special precautions required.
: Do not stock unsupported sheet or pallets too high.

LEXAN® THERMOCLICK / THERMOCLEAR® SHEET

Revision : 04/08/1998,

Supersedes issue : na

Page : 3/4

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure controls	: A continuous supply of fresh air to the workplace, together with removal of processing fumes through exhaust systems is recommended.
Personal Protection	
- Eye/face	: Wear safety glasses with side shields when cutting the sheet.
- Respiratory	: Good industrial hygiene practice requires adequate general ventilation of the workplace. When dust and powder from secondary operations, such as grinding, sanding or sawing are not adequately controlled, use respirator approved for protection from dust.
- Hands	: Wear protective gloves when handling the sheet, as the edges may be sharp.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Solid
Odour and appearance	: Multi-wall plastic sheet with slight or no odour
Boiling point	: Not applicable
Melting point	: See comment below
Vapor pressure (mmHg)	: Negligible
Vapor density (air=1)	: Not applicable
Specific gravity (water=1)	: >1
Water solubility	: Insoluble
% Volatiles	: Negligible
pH	: Not applicable
Odour threshold	: Not established
Evaporation rate	: Negligible
Coefficient water/oil distr.	: Not established
Flash point	: Not applicable
Lower flammable limit	: Not established
Upper flammable limit	: Not established
Autoignition	: 630 °C, estimated
Comment	: This product does not exhibit a sharp melting point, but softens gradually over a wide temperature range.

10. STABILITY AND REACTIVITY

Stability	: Stable under recommended conditions of storage and handling.
Reactivity	: Not reactive under recommended conditions of handling, storage, processing and use.
Hazardous Decomposition	: Processing fumes evolved at recommended processing conditions may include trace levels of phenol, alkyl phenols and diarylcarbonates.

LEXAN® THERMOCLICK / THERMOCLEAR® SHEET

Revision : 04/08/1998,

Supercedes issue : na

Page : 4/4

11. TOXICOLOGICAL INFORMATION

Product

- Acute oral : Oral LD50 (rat) > 5 g/kg, estimated.

12. ECOLOGICAL INFORMATION

General

: Not expected to present any significant ecological problems.

13. DISPOSAL INFORMATION

Waste disposal

: This product is not regarded as hazardous waste.
: Dispose in accordance with local regulations.

Recycling:

: This product may be recycled either back into sheet, or into other suitable applications.
: Please consult your local GE Plastics sales office for advice.

14. TRANSPORTATION INFORMATION

General

: This product is not subject to transport regulations.

15. REGULATORY INFORMATION

This product is not considered dangerous under EC Directives 67/548/EEC and 88/379/EEC, as amended.

This MSDS has been prepared in accordance with EU Directive 91/155/EEC, as amended by 93/112/EC.

16. OTHER

This publication provides information and guidelines for safe handling and cutting of GE Plastic's sheet and is based on currently available experience and knowledge. It is not designed as a comprehensive product performance data sheet, nor as a guide to application possibilities of our materials.

Users should follow all applicable local regulations governing Health and Safety at work, and are requested to pass this publication on to all relevant employees and customers.

LEXAN® and **THERMOCLICK / THERMOCLEAR®** are registered trademarks of the GENERAL ELECTRIC COMPANY or it's affiliates.